

## OZZY VARIABLE V-BLADE

Light plough with variable geometry designed for patrol clearing of sidewalks, squares, parks, narrow streets.

### MOUNTING SYSTEM:

- standardized coupling plate,
- TPH,
- SMS.



### FEATURES

- metal plough protected against corrosion,
- wear resistant rubber cutting edge,
- spring swing bottom-trip system protecting against obstructions,
- float mode
- LED marker lights,
- work function control: lifting / lowering, working with spoon, working with bow, one-sided ploughing
- driven with independent power pack or carrier's hydraulic

### SPECIFICATION

PARAMETER	VALUE
Width of the plough	2500-3000 mm
Clearance width	2100-2500mm
Height of the plough	800 mm
Weight of the plough	300-350kg



## OZ-K SNOWPLOUGH

Designed for mounting on a backhoe-loaders and tractors.

### FEATURES

- metal plough protected against corrosion,
- durable rubber cutting edge,
- side fenders,
- LED marker lights,
- controlling functions from carrier's hydraulic.

### SPECIFICATION

PARAMETER	VALUE
Width of the plough	2800 mm
Clearance width	2404 mm
Height of the plough	1100 mm
Clearance angle	+/- 30°
Weight of the plough	435 kg



### MOUNTING SYSTEM:

- mount to backhoe-loader,
- TPH,
- SMS.

## OZ- DZ VARIABLE V-BLADE

Specialized heavy plough with a variable geometry designed to work under severe weather conditions.

### FEATURES

- metal plough protected against corrosion ended at the bottom with metal cutting edges in cutting position,
- special wings profile limiting rejection of snow on the carrier's cabin, providing driver with safety and comfort,
- hydraulic override protection against obstacles,
- power pack mounted on the plough, powered by 24VDC carrier,
- control of all functions with control panel mounted in driver's cab: lifting / lowering, working with spoon, working with bow, one-sided ploughing, floating position (required 3 pairs of input / output).
- road lighting and LED marker lights.

### MOUNTING SYSTEM:

- standardized coupling plate,
- TPH,
- mount on backhoe-loader.

### SPECIFICATION

PARAMETER	VALUE
Width of the plough	3500 mm
Clearance width	2200-2800 mm
Height of the bow	850 mm
Height of rear wings	1300 mm
Weight of the plough	900 kg



## OZ-TR SNOW PLOUGH

2-segment snow plough for tractors.

### FEATURES

- metal 2-segment blade protected against corrosion,
- steel or rubber cutting edge,
- spring swing full-trip system protecting against obstructions,
- TPH mount cat. 2/3
- driven with carrier's hydraulic

### SPECIFICATION

PARAMETER	VALUE
Width of the plough	3200 mm
Clearance width	2900 mm
Height of the plough	1000 mm
Clearance angle	+/- 30°
Weight of the plough	520 kg



# SNOW PATROL SNOW PLOUGH

Snow Patrol is a light blade, which can be attached to 4x4 trucks, pick-ups and SUV. It is particularly designed for snow clearing off drive ways, pavements, parking areas and narrow streets. Snow removal job becomes an easier and more efficient as Snow Patrol is a robust and reliable tool.

## FEATURES:

- metal construction protected against corrosion,
- flexible and durable plastic mouldboard resistant to low temperatures and impacts,
- wear resistant rubber cutting edge,
- 12VDC power pack and wireless control,
- control all functions of the plough with the control panel mounted in driver's cab: raising and lowering, angling left / right, floating position, down pressure mode,
- LED marker lights.

## SPECIFICATION

PARAMETER	VALUE
Width of the plough	2250 mm
Clearance width	1957 mm
Height of the plough	750 mm
Clearance angle	+/- 30°
Weight of the plough	200 kg



# DELTA VARIABLE V-BLADE

Light plough with variable geometry designed for patrol clearing of roads, squares, parking lots

## FEATURES

- metal plough protected against corrosion,
- wear resistant rubber cutting edge,
- spring swing bottom-trip system protecting against obstructions,
- float mode
- LED marker lights,
- work function control: lifting / lowering, working with spoon, working with bow, one-sided ploughing
- driven with independent power pack or carrier's hydraulic

## SPECIFICATION

PARAMETER	VALUE
Width of the plough	2700-3200 mm
Clearance width	2200-2900 mm
Height of the plough	924-1066 mm
Weight of the plough	420-600 kg



**MOUNTING SYSTEM:**  
 -standardized coupling plate,  
 -TPH,  
 -SMS.

# OZKA SPREADERS FOR TRACTORS

Hydraulic, mounted on TPH, self-loading

## FEATURES

- hydraulically driven,
- dosage regulation,
- lump actuator
- chain transmission
- supporting legs
- TPH mount cat. 2

## SPECIFICATION

PARAMETR	WARTOŚĆ
Spread width	1800 mm
Hopper capacity	1000 L
Weight	500 kg

